

- Fan-assisted refrigeration display and storage
- Superior performance and European styling
- Six sizes available External corners available
- Units supplied standard with internal stainless steel finish and hydraulic lift-up glass
- Easy clean and food safe environment
- Advanced ventilated cooling system
- Curved, toughened safety glass
- Heavy duty castors (feet required for multiplexing)
- Rear Perspex doors
- Rear stainless steel work bench
- Colour: Silver fascia panels
- 10 Amp power outlet required
- Rear cold underbench storage with doors
- Multiplexable - can be joined to create one long, seamless counter
- Units supplied with castors and adjustable legs
- Assembly may be required, please contact us



Ideal for:

- . Cafes
- . Juice Bars
- . Restaurants
- . Hotels and Resorts
- . Supermarkets
- . Take-aways

Options:

- Glass shelf
- Sandwich/Salad Bar (see following page)
- Bain Marie (see following page)
- 90° spherical corner - fan assisted built-in refrigeration
- 45° External spherical corner (not refrigerated)
- Multiplexing

	DD0150P LED	DD0200P LED	DD0250P LED	DD0290P LED	DD090P LED	DD045P LED
Bromic Part Number	3335600	3335601	3335602	3335603	3335604	3335605
Display Area m²	1.15 m ²	1.56 m ²	1.97 m ²	2.3 m ²	0.96 m ²	0.48m ²
External Dimensions (mm)	1500w x1123d x 1389h	2000w x1123d x 1389h	2500w x1123d x 1389h	2900w x1123d x 1389h	see below for width & depth x 1389h	see below for width & depth x 1389h
<small>Depth dimensions exclude lightbox and handle protrusions</small>						
Temperature range (°C)	0 to +10°C	0 to +10°C	0 to +10°C	0 to +10°C	0 to +10°C	N/A
Max. ambient temp °C/RH%	32°C/60%	32°C/60%	32°C/60%	32°C/60%	32°C/60%	N/A
Refrigeration Power (Watts)	709W	1160W	1374W	1650W	709W	N/A
Plug Supplied	Yes, 10amp	Yes, 10amp	Yes, 10amp	Yes, 10amp	Yes, 10amp	Yes, 10amp
Front glass hydraulic lift up system	Yes	Yes	Yes	Yes	Yes	Yes
Internal Tray Width base shelf (mm)	818	818	818	818	818	818
Interior light	LED	LED	LED	LED	LED	LED
No. Of Doors	2 Sliding	4 Sliding	4 Sliding	4 Sliding	2 Lift Off	Lift Off
Door Lock	No	No	No	No	No	No
Temperature Display	Digital	Digital	Digital	Digital	Digital	Digital
Gross weight (kg)	178kg	228Kg	278Kg	320kg	200Kg	150Kg
Refrigerant	R404a	R404a	R404a	R404a	R404a	R404a
Colour	Silver	Silver	Silver	Silver	Silver	Silver
Power Usage (at 30 °C/60%RH)	18kWh/24hr	22kWh/24hr	26kWh/24hr	27kWh/24hr	17kWh/24hr	N/A

Refer to page 74 for pre-installation checklist

WARRANTY 1 YR PARTS YR LABOUR

